

AC/DC Power Adaptor EXA0601 series



Features

- Output range: 5W~12W
- No Load Power Consumption <math><0.5\text{W}</math>, meet C.E.C. & I.E.C. standard
- Operating Temperature $0^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Option: LED Indicator
- Over Voltage Protection
- Over Current Protection
- Short Circuit Protection

Power the green world



MODEL		EXA0601UA/EA/CA/BA/AA	EXA0601UB-1/EB-1/CB-1/BB-1/AB-1	EXA0601UB-2/EB-2/CB-2/BB-2/AB-2
OUTPUT	Output Voltage	5V	12V	
	Maximum Output Voltage	1A	0.5A	1A
	Output Power	5W	6W	12W
	Ripple & Noise	50mVp-p	120mVp-p	
	Efficiency	65%	72%	75%
	Output Voltage Tolerance	±5%		
	Hold-up Time	8ms		
PROTECTION	Input Voltage Range	90~264Vac		
	Frequency	47~63Hz		
	No Load Power Consumption	< 0.5W		
	Over Voltage Protection	Yes		
	Over Current Protection	Yes		
	Short Circuit Protection	Yes		
ENVIRONMENT	Safety Approval	c-UL, TUV, CCC, CE, CB		
	Operating Temperature	0°C~ + 40°C		
	Operating Humidity	5%~95% RH		
	Storage Temperature	- 20°C ~ + 85°C		
	Storage Humidity	10% ~ 90% RH		
	Vibration	Operating:10-250Hz, 0.25G peak to peak, 3 axes, 15 min weep. Storage: 10-300Hz, 2.0G peak to peak, 3 axes, 15 min sweep.		
	MTBF	50000 hours		
OTHERS	Dimension	(WxHxL) 29.1x44.4x64.5(mm)		
	Output Connector	USB mini-B or DC plug 2.1x5.5x9.5 (mm)		
	AC Plug	USA/ Europe/ China/ UK/ Australia		



Enertronix, Inc.

6F, No. 1, Alley 30, Lane 358.
 Ruiguang Rd. Neihu 114. Taipei. Taiwan
 T: +886-2-2658-6176
 F: +886-2-2658-9332
 sales@enertronix.com.tw

Power the green world

