

AC/DC Power Adaptor EXA0604 series



Features

- Output Range: 9W~18W
- Hold-up Time $\geq 16\text{ms}$
- Surge Immunity, IEC 61000-4-5: $\pm 2\text{KV}$
- No Load Power Consumption $< 0.5\text{W}$,
Meet C.E.C. & I.E.C. Standard
- Operating Temperature $0^{\circ}\text{C} \sim + 40^{\circ}\text{C}$
- Over Voltage Protection
- Over Current Protection
- Short Circuit Protection

Power the green world



ITEM		MODEL						
		EXA0604UD/ED	EXA0604UA-1/EA-1	EXA0604UB-1/EB-1	EXA0604UA-2/EA-2	EXA0604UC/EC	EXA0604UB-2/EB-2	EXA0604UE/EE
OUTPUT	Output Voltage	9V	5V	12V	5V	15V	12V	18V
	Maximum Output Voltage	1A	2A	1A	2.5A	1A	1.5A	1A
	Output Power	9W	10W	12W	13W	15W	18W	
	Ripple & Noise	120mVp-p				150mVp-p	120mVp-p	150mVp-p
	Efficiency	72%	70%	75%	70%	75%		
	Output Voltage Tolerance	±5%						
	Hold-up Time	16ms						
PROTECTION	Input Voltage Range	90~264Vac						
	Frequency	47~63Hz						
	No Load Power Consumption	< 0.5W						
	Over Voltage Protection	Yes						
	Over Current Protection	Yes						
	Short Circuit Protection	Yes						
ENVIRONMENT	Safety Approval	c-UL, TUV, CE, CB						
	Operating Temperature	0°C ~ + 40°C						
	Operating Humidity	5%~95% RH						
	Storage Temperature	- 20°C ~ + 85°C						
	Storage Humidity	10% ~ 90% RH						
	Vibration	Operating:10-250Hz, 0.25G peak to peak, 3 axes, 15 min weep. Storage: 10-300Hz, 2.0G peak to peak, 3 axes, 15 min sweep.						
	MTBF	50000 hours						
OTHERS	Dimension	53x35.4x72.1(mm)						
	Output Connector	DC plug 2.1x5.5x9.5 (mm)						
	AC Plug	USA/ Europe						



Enertronix, Inc.

6F, No. 1, Alley 30, Lane 358.
 Ruiguang Rd. Neihu 114. Taipei. Taiwan
 T: +886-2-2658-6176
 F: +886-2-2658-9332
 sales@enertronix.com.tw

Power the green world

